

RENOLIN 500 Series VDL-Air Compressor Oils and Gas Compressor Oils

Description

RENOLIN 500 Series can be used in air compressors and can also be used in compressors working with hydrocarbon gas e.g. natural gas (different composition), propane, propen and process gas.

The products of the RENOLIN 500 Series are air compressor oils for piston and rotation compressors according to DIN 51506 Type VDL. The RENOLIN 500 Series is formulated on the basis of especially highly refined base oils; the additives select make possible reliable use at high thermal stress without the formation of damaging residue.

Intensified laboratory tests and many years of experience with use confirm the extraordinary oxidation stability of these special compressor oils.

Applications

Air compressor oil for all piston and rotation compressors according to DIN 51506, VDL for final compression temperatures up to 220 °C.

If other media are compressed, please contact our Application Engineering Department. Manufacturer specifications have to be complied with.

Advantages

- **Excellent oxidation and thermal stability**
- **Low coking**
- **Minimal foaming**
- **Good air release capacity**
- **Protects against wear and corrosion**
- **Very low evaporation tendency**
- **Final compression temperatures up to 220 °C**

Specifications

The products of the RENOLIN 500 series meet and in many cases exceed the requirements:

DIN 51506: VDL

VDL according to TÜV Certificates

RENOLIN 500 Series VDL-Air Compressor Oils and Gas Compressor Oils

Typical technical data:

Product name		503	504	505	506	
Properties	Unit					Test method
ISO VG		68	100	150	220	DIN 51519
DIN 51506 VDL requirements		fulfilled	fulfilled	fulfilled	fulfilled	DIN 51506
Kinematic viscosity at 40 °C	mm ² /s	68	100	150	230	DIN EN ISO 3104
at 100 °C	mm ² /s	9.1	10.7	15.0	18.7	
Viscosity index	-	109	90	100	90	DIN ISO 2909
Density at 15 °C	kg/m ³	867	890	883	893	DIN 51757
Color index	ASTM	0.5	1.0	1.5	2.0	DIN ISO 2049
Flash point in open cup according to Cleveland	°C	250	280	275	280	DIN ISO 2592
Pour point	°C	-18	-21	-15	-12	DIN ISO 3016
Neutralization number	mgKOH/g	0.13	0.13	0.13	0.13	DIN 51558

Product Information

MOVING YOUR WORLD



Note

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH.

© FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved.