

## TITAN CARGO MC SAE 10W-40

**Premium Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.**

### Description

TITAN CARGO MC 10W-40 is a super long-life, fuel-economy engine oil for all diesel engines with and without turbocharger in trucks, buses and industrial machinery. The SAE Class 10W-40 ensures reliable all-season use. Suitable for the longest oil change intervals.

### Application

TITAN CARGO MC 10W-40 has a higher performance capacity than the usual high-performance engine oils. Internationally, this type of oil is designated as UHPD (UHPD = Ultra High Performance Diesel Oil). Regardless of the current service life, even older diesel engines can be changed over to TITAN CARGO MC 10W-40 without flushing. Protects against corrosion even when high sulfur-content diesel fuels are used. The performance of TITAN CARGO MC 10W-40 makes extremely long oil change intervals possible based on the truck manufacturer's recommendations. According to the new Mercedes Benz fluids specifications MB APPROVAL 228.5, an extended oil change interval is guaranteed for trucks in long-distance and local use for the 900 and 500 engine series. TITAN CARGO MC 10W-40 is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN CARGO MC 10W-40. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

### Advantages/Benefits

- Reduced fuel consumption due to fuel-economy characteristics.
- High wear protection even under continuous stress at full engine load. Protects against mirror surface formation on cylinder races.
- Fastest possible oil circulation after start; this reduces cold-start and warm-up wear.
- Reduces exhaust gas particulates.
- Reliable protection against deposits, sludge and adhesion during extremely high thermal stress and stop-and-start driving.
- Optimum compatibility with seal materials.
- Environmentally friendly due to the longest oil change intervals and low evaporation losses.

### Specifications

- ACEA E7/E4
- API CI-4
- GLOBAL DHD-1
- JASO DH-1

### Approvals

- CUMMINS CES 20077/8
- DETROIT DIESEL 93K215
- DEUTZ DQC III-18
- MACK EO-N
- MAN M 3277
- MB-APPROVAL 228.5
- MTU DDC TYPE 3
- RENAULT RLD-2
- VOLVO VDS-3

PI60873e, PMA, 19.05.2022, Page 1

# Product Information

*MOVING YOUR WORLD*



## FUCHS Recommendations

- ALLISON C-4
- FORD WSS-M2C944-A
- IVECO 18-1804
- SDFG OM-1901A

PI60873e, PMA, 19.05.2022, Page 2

# Product Information

*MOVING YOUR WORLD*



## TYPICAL CHARACTERISTICS

---

Density at 15 °C	DIN 51757	0.871 g/ml
SAE Grade	SAE J300	10W-40
Kinematic Viscosity at 40°C	DIN 51562-1	92.8 mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	DIN 51562-1	14.2 mm <sup>2</sup> /s
Viscosity index	DIN ISO 2909	157
HTHS	CEC L-036-90	≥ 3.5 mPa*s
Pour Point	DIN ISO 3016	-42 °C
Sulphated ash	ASTM D874	≤ 2.0 % m/m
Product dyeing	DIN 10964	none

PI60873e, PMA, 19.05.2022, Page 3

# Product Information

*MOVING YOUR WORLD*



## Note

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH.

© FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved.